

AN 10/733,160  
Page 3

**Amendments to the Claims:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

**Listing of Claims:**

Claim 1. (Original) A linear engaging headless fastener system comprising:  
a body member having an outer surface positioned about a central axis, said body member having a first end including a cavity, said cavity having an engaging surface, said engaging surface tapering inwardly from about said first end and extending toward a second end, said second end defining a clamping surface adapted to provide a clamping force to an assembly;

an expander member having a first end, a second end, and an outer surface positioned about a central axis, said outer surface tapering outwardly from said first end and extending toward said second end, said first end being insertable into said body member cavity;

whereby said outer surface of said expander member is constructed and arranged for coaxial alignment and engagement with respect to said engaging surface of said body member, said expander member being linearly traversable with respect to said engaging surface of said body member between a first release position and a second engaged position, wherein said engaged position results in said tapered surfaces circumferentially expanding said body member to provide compression loading of said expander member, wherein said body member outer surface engages an aperture having an inner gripping surface, and wherein said release position results in circumferential contraction of said body member outer surface thereby releasing said inner gripping surface of said aperture.

AN 10/733,160  
Page 4

**Claim 2. (Original)** The linear engaging fastener system of claim 1 including means projecting radially from said outer surface of said body member outer surface for engagement with said inner surface of said aperture for locking said body member in a predetermined position.

**Claim 3. (Currently Amended)** The linear engaging fastener system of claim 2 wherein said radially projecting means includes at least one outwardly and circumferentially extending rib, each said rib including a first ramp surface to facilitate coaxially aligned linear movement of said ~~fastener body member~~ in relation to said inner gripping surface of said aperture to provide a secondary clamping force upon engagement of said expander member.

**Claim 4. (Currently Amended)** The linear engaging fastener system of claim 3 wherein said at least one circumferentially extending rib includes a second ramp surface to facilitate coaxially aligned linear insertion of said ~~fastener body member~~ into said inner gripping surface of said aperture.

**Claim 5. (Original)** The linear engaging fastener system of claim 4 wherein said radially projecting means are helical threads.

**Claim 6. (Original)** The linear engaging fastener system of claim 2 wherein said radially projecting means define a knurled surface.

**Claim 7. (Original)** The linear engaging fastener system of claim 1 wherein said first end of said body member includes at least one driving surface, said at least one

AN 10/733,160  
Page 5

driving surface constructed and arranged to cooperate with a driving tool for providing rotational force to said body member.

Claim 8. (Original) The linear engaging fastener system of claim 7 wherein said at least one driving surface is adapted to cooperate with a screwdriver.

Claim 9. (Original) The linear engaging fastener system of claim 1 wherein said first end of said body member includes a plurality of driving surfaces, said plurality of driving surfaces constructed and arranged to cooperate with a driving tool for providing rotational force to said body member.

Claim 10. (Original) The linear engaging fastener system of claim 9 wherein said plurality of driving surfaces are adapted to cooperate with a hex shaped tool.

Claim 11. (Original) The linear engaging fastener system of claim 1 wherein said clamping surface is selected from the group consisting of flat point, dog point, half dog point, cup point, oval point, cone point or knurled point.

Claim 12. (Original) The linear engaging fastener system of claim 1 wherein said body member is constructed of metal.

Claim 13. (Original) The linear engaging fastener system of claim 1 wherein said body member is constructed of polymeric material.

Claim 14. (Original) The linear engaging fastener system of claim 1 wherein said body member is constructed of rubber.

AN 10/733,160  
Page 6

Claim 15. (Original) The linear engaging fastener system of claim 1 wherein said engaging surface within said cavity is a self-locking taper.

Claim 16. (Original) The linear engaging fastener system of claim 16 wherein said self-locking taper is selected from the group consisting of MORSE, BROWN & SHARPE, JARNO, AMERICAN NATIONAL STANDARD MACHINE, JACOBS and BRITISH STANDARD.

Claim 17. (Currently Amended) The linear engaging fastener system of claim 1 wherein said expander member includes at least one internal bore extending inwardly from said first end of said expander member along a longitudinal centerline, wherein said at least one internal bore is constructed and arranged for gripping and placing a tensile load on said expander member prior to linear traversal of said expansion member into said ~~disengaged~~release position with respect to said body member.

Claim 18. (Original) The linear engaging fastener system of claim 17 wherein said internal bore includes internal threads.

Claim 19. (Original) The linear engaging fastener system of claim 1 wherein said outer surface of said expander member includes a self-locking taper.

Claim 20. (Original) The linear engaging fastener system of claim 19 wherein said self-locking taper is selected from the group consisting of Morse, Brown & Sharpe, Jarno, American National Standard Machine, Jacobs and British Standard.

AN 10/733,160  
Page 7

Claim 21. (Original) The linear engaging fastener system of claim 19 wherein said outer surface of said expander member and said inner engaging surface of said body member are constructed and arranged to maintain an axially aligned interfitting relationship in said release position.

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☒ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**